

Surface grinder



- Supplied with magnetic chuck
- Fitted with one shot centralised lubrication to slideways and leadscrews
- Diamond wheel dresser supplied
- Single phase electrics
- Complete with cabinet

Item No. 2013YZ	
SPECIFICATION	
Table surface area	305x152mm
Table traverse	320mm
Table cross traverse	170mm
Grinding wheel size	178x31.7x12.7mm
Max. distance from wheel ctr to table	280mm
Min. distance from wheel ctr to table	89mm
Vertical feed per spindle revolution	0.04/0.08/0.14
Spindle speed	3600rpm
Spindle motor	560w/240v
Floor space	440x430mm
Overall dimensions LxWxH with stand	930x780x1430mm
Weight	226kg

Universal cutter grinder

Compact, versatile grinder. Suitable for HSS and carbide tools. Optional tooling will accommodate end mills, twist drills or lathe tools.

- Supplied to accept either R8 or 5C collets.
- Single phase
- 24 position universal head
- See collet selection on page 115



Item No. 2020R8/20205C	
SPECIFICATION	
Collet capacity	
R8	20mm
5C	28mm
Maximum grinding diameter	25mm
Taper angle	0° - 180°
Relief angle	0° - 44°
Negative angle	0° - 52°
Spindle speed	5200 rpm
Cup grinding wheel	100x50x20mm
Motor	240v
Dimensions LxWxH	450x400x350mm
Weight	45kg


Replacement silicone wheel
Item No. 9526



Diamond replacement wheel
Item No. 5577



Diamond cup wheel
Item No. 5577A




OPTIONAL TOOLING


Twist drill holder
Item No. 55745C
Item No. 5574R8



End mill holder
Item No. 55755C
Item No. 5575R8



Lathe tool holder
Item No. 55765C
Item No. 5576R8



Diamond wheel dresser
Micro adjustment
Item No. 5575

