

Machine: 4062 / 4062A	GH1439 VARIANTS
<u>Product Dimensions:</u>	
Weight	700kg
Width x Depth x Height	1815 X 680 X 1485mm
Tray Length x Width	1815 X 505mm
<u>Shipping Dimensions</u>	
Length x Width x Height (DRO version)	1930 X 755 X 1530mm
<u>Power/Motor</u>	
Motor size	1.8kw
Power Transfer (GH) gearbox or (VS) variable speed	GH
Spindle speeds (No: and achievable speeds)	8 Speeds, 70,125,190,300,460,755,1255,2000
Voltage (240v single) (440v 3 Phase)	240v and 3 Phase available
Fitment (Plug connection type)	3 pin plug or cables
Current	50hz, 6A
<u>Main Specifications</u>	
Maximum swing	340mm
Centre height	170mm
Distance between centre's	1000mm
Longitudinal travel (Z)	775mm
Cross slide travel (X)	175mm
Top slide travel (fine Z)	95mm
Spindle taper	6MT
Tailstock Taper	3MT
Tailstock quill travel	100mm
Spindle Bore	52mm
Tool shank size recommended for C/L	16mm
Metric and imperial threads	0.4-7mm , 56-4TPI
Chuck mount	D1-5 Camlock
Spindle Bearings/Drive	Taper Roller
<u>Other Specifications</u>	
Country of origin	China
Warranty	12 Months
Approximated assembly and setup time	45 mins
CE approved Certificate	Yes, available upon request

Machine Data Sheet

Additional products	
Optional stand	N.A
Optional Digital Read Out Kit	8123
X scale	200mm
Z Scale	800mm
Chuck mount sizes	D1-5 Camlock
Base/tray fixing holes dimensions A-B-C-D	A= 350 B= 250 C= 1300 D= 85mm

